

2-Stage Wall mount 20" Water Conditioner with 5-micron Carbon Block Cartridge and ScaleGon™ Conditioning cartridge

Features and Benefits

- Removes Sediment

H2OG-ScaleGon™:

- Extremely Efficient- 5 Second Contact Time. Regardless Of Hardness Level.
- No Salt Or Other Chemical Regenerants Required
- No Backwash Waste
- Can Be Used In Areas Where Softeners Are Banned
- Protects The Environment And Reduces Water Usage
- Long Lasting Media (Not depleted by reactions)
- No Control Valve Or Electricity Required
- Replaceable cartridge system
- Media Operates In Up-flow Condition

System Specifications

Input/ Output Connection - 3/4"
Operating Pressure - 6 Bar (90 PSI)
Maximum Recommended Pressure - 80 - 100 PSI
Minimum Recommended Pressure - 40 PSI
Flow Rate - 4-8 Gallons per Minute
Filter Cartridge Size - 4.5" x 20"
Filter Life: 6-9 Months or as needed.

Cartridge Breakdown

	H2OG-SG2-4520
Stage 1	5 mic Carbon Block
Stage 2	H2OG-SG-4520 Cart.



H2OGUARD™ IS A TRADEMARK OF H2O INTERNATIONAL INC.
3001 S.W. 15th Street Suite C, Deerfield Beach FL 33442 USA